



WELL Gobo

WELL Gobo is a compact, outdoor-ready, battery-powered gobo projector ideal for corporate and event rental inventories. Compatible with both glass and metal gobos, the unit also features a manual 20 to 41-degree zoom and framing shutters for flawless shutter cuts. Set it then forget it with onboard OLED display, and control your way with WDMX to link to WELL COM. WELL Gobo includes multiple mounting options and comes in a pack of 4 with a self-charging case.



At a Glance

- A completely wireless, IP 65 rated, battery powered Gobo Projector with a cool white LED and manual framing shutters that is controlled by W-DMX, IR remote (not included), or manually from the OLED display
- Zoom range of 20° to 41° making sizing patterns on surfaces easy
- Hard and soft focuses are easily achieved
- Works with both glass and metal E size gobos (1 mm max thickness)
- User selectable PWM settings to ensure flawless on camera operation
- M12 hole for easy clamp installation
- Up to 8 hours of operational time on full charge
- Recharging case can be power linked to save on power outlets
- Recharging case can be charged with the lid closed saving warehouse space

Specifications

Optical

- Light Source: 1 LED (CW) 25.2 W, (1.3 A), 6542 K, 50,000 hours life expectancy.
- Color Temperature (at full): 6542 K
- Lumens: 2892
- CRI: 79.1
- Beam Angle: 17.3° to 36.6°
- Field Angle: 20° to 41°
- Zoom Angle: 20° to 41°
- Illuminance (17.3°): 1,487 lux @ 5 m
- Illuminance (8 hr mode 17.3°): 1,487 lux @ 5 m
- Illuminance (36°): 347 lux @ 5 m
- Illuminance (P/S mode 36°): 165 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Dynamic Effects

- Manual Tilt: 180°
- Tilt Ranges: 0° to 180° tilt
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Manual
- Focus: Manual
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

Construction / Physical

- Dimensions (Single Unit): 10.11 x 6.81 x 12 in (257 x 173 x 305 mm)
- Dimension (Charging Case): 27.64 x 17.24 x 23.36 in (702mm x 438 x 593.4 mm)
- Weight (Single Unit): 6.6 lb (3 kg)
- Weight (Charging Case): 71 lb (32.21 kg)
- Exterior Color: Black
- Housing Material (Single Unit): Aluminum diecast
- Housing Material (Charging Case): Aluminum alloy, wood
- Gobo Size (Optional): "E": 37.5 mm (outside), 24 mm (image), 1 mm (max. thickness)

Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon
- Power Input: Seetronic Powerkon
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: W-DMX, IRC
- DMX Channels: 1, 2, 3 or 6

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 9 units @ 120 V; 15 units @ 208 V; 16 units @ 230 V
- Power and Current (single unit charging): 42 W, .345 A @ 120 V, 60 Hz
- Power and Current (charging case): 168 W, 1.38 A @ 120 V, 60 Hz
- Power and Current (single unit charging): 48 W, 0.220 A @ 208 V, 60 Hz
- Power and Current (charging case): 192 W, 0.880 A @ 208 V, 60 Hz
- Power and Current (single unit charging): 49 W, 0.211 A @ 230 V, 50 Hz
- Power and Current (charging case): 196 W, 0.844 A @ 230 V, 50 Hz

Battery

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 8 hours
- Battery Life: 5 hrs (high output), 8 (power saving mode)
- Battery Power: 29.6, 4400 mAh

Certifications / Qualifications

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use

What's Included

- (4) WELL Gobo
- Charging Case
- powerCON power cable with Edison plug
- (4) Gobo holder